


# ANS-12002/12003

Compact Fan-less System with Intel® Amston Lake x7433RE(4C)/ x7835RE(8C) Processor for SD-WAN solution



## FEATURES

- ANS-12000 series builds on Intel® Amston Lake x7405C / x7809C
- Up to 8 Efficient Cores (E-cores) and support Intel DL Boost (INT8), AVX2
- 1x DDR5 4800 MT/s ECC and non-ECC SO-DIMM up to 32GB
- 2x SIM slots 1x M.2 Key-M 2242 slot (SATA) 1x M.2 Key-E 2230 slot (PCIe + USB 2.0) or M.2 2242/2280 (NVME) choose one of two \* 1x M.2 Key-B 3042/3052 slot
- 1x TPM 2.0 (On-Board) Design ready for 5G and WiFi

## General

|                |                                                                                          |
|----------------|------------------------------------------------------------------------------------------|
| Processor      | Intel® 9th Gen Atom Amston Lake x7405C(4C)<br>Intel® 9th Gen Atom Amston Lake x7809C(8C) |
| BIOS           | AMI uEFI BIOS                                                                            |
| Memory         | Support up to 16GB on 1 non-ECC/ECC SODIMM                                               |
| Storage        | 1 x 2.5" SSD/HDD 2242 Slot (SATA)<br>1 x eMMC 32G on board                               |
| Watchdog Timer | Programmable, time out period from 1 s to 255 s                                          |

## Rear I/O

|              |                                                                         |
|--------------|-------------------------------------------------------------------------|
| Ethernet     | 4 x 2.5 GbE w/ Intel WGI226IT Bypass<br>1 x GbE w/ Intel WGI210IT Combo |
| USB          | 1 x USB 3.2 Gen1 Type A on Rear                                         |
| Other        | Power Button, Reset Button                                              |
| Console Port | 1 x RJ45                                                                |
| LED          | Bypass, ETH Status, HDD, Power, RSSI, WiFi                              |
| Antenna      | SMA Antenna holes for 5G / LTE / WiFi                                   |
| SIM Slots    | 2 x Micro-SIM                                                           |

## Ordering Guide

|           |             |                                                                                                                                       |
|-----------|-------------|---------------------------------------------------------------------------------------------------------------------------------------|
| ANS-12002 | Category    | csn_system                                                                                                                            |
|           | Product     | ANS-12002                                                                                                                             |
|           | Description | ANS-12002-x7405C. ASL x7405C SKU, Proprietary Fan System. With PNAB-1210-x7405C. 12V Input. 2.5GbE RJ45*4. 1GbE SPF*1. DDR5 SO-DIMM*1 |
|           | P/N         | AS5-3689                                                                                                                              |
|           | Status      | Available                                                                                                                             |
| ANS-12003 | Category    | csn_system                                                                                                                            |
|           | Product     | ANS-12003                                                                                                                             |
|           | Description | ANS-12003-x7809C. ASL x7405C SKU, Proprietary Fan System. With PNAB-1210-x7405C. 12V Input. 2.5GbE RJ45*4. 1GbE SPF*1. DDR5 SO-DIMM*1 |
|           | P/N         | AS5-3678                                                                                                                              |
|           | Status      | Available                                                                                                                             |

## Expansion I/O

|          |                                                                                                           |
|----------|-----------------------------------------------------------------------------------------------------------|
| M.2      | 1 x E Key w/ 3042 USB 2.0 and PCIe x1<br>1 x M Key 2242/2280 PCIe Gen3 x4 or 1 x B+M Key 2230 WiFi module |
| Security | TPM 2.0                                                                                                   |

## ME/Environment

|                          |                                                   |
|--------------------------|---------------------------------------------------|
| Dimension(WxDxH)         | 200 x 255 x 44 mm (7.87" x 10.04" x 1.73" )       |
| Weight                   | 1.7 kg                                            |
| Power Supply             | DC Jack 12V Single                                |
| Mounting                 | Desktop, Wall Mount                               |
| Operating Temperature    | 0 ~ 40 °C (32.0 ~ 104.0 °F)                       |
| Storage Temperature      | -40 ~ 70 °C (-40.0 ~ 158.0 °F)                    |
| Cooling                  | System 2 x Fan                                    |
| Relative Humidity        | 5% to 90%, non-condensing                         |
| Certification            | CE, FCC Class B Part18, CE LVD Safety (EN32638-1) |
| Portwell Special Feature | PET, NODE.X                                       |

\*Choose one of three with M.2 Key-E 2230 slot, SFP, and M.2 Key-M 2242/2280 slot