

APA-2020

250W 1U ATX Power Supply

FEATURES

- Full-range AC input: 100 Vac-240 Vac
- Low ripple & noise output
- Support OVP, SCP and OCP
- Safety certifications: CE, FCC, UL, TUV, CCC
- Dimension: 100 x 40.5 x 190 (mm)



SPECIFICATION

Input Voltage	100 Vac-240 Vac
Wattage	250W
Form Factor	1U
MTBF(hrs)	100,000 @25°C
Temperature/Humidity	Operating: 5°C ~ 50°C, 20%~80%RH Storage: -20°C ~ 80°C, 10%~95%RH
EMC & Safety	CE, FCC, UL, TUV, CCC
Dimension (WxHxD)	100 x 40.5 x 190 (mm)

DC OUTPUT

	+5V	+3.3V	-5V	+12V	-12V	+5Vsb
Max. Load	24A	20A	0.5A	12A	0.5A	1.5A
	170W					
Min. Load	3A	1A	0A	2A	0A	0.1A
Ripple	50mv	50mv	100mv	80mv	100mv	50mv

APA-3083

400W 1U ATX Power Supply

FEATURES

- Full-range AC input: 100 Vac-240 Vac
- Low ripple & noise output
- Support OVP, SCP and OCP
- Safety certifications: CE, FCC, UL, CSA, TUV, CCC
- Dimension: 100 x 40.5 x 190 (mm)



SPECIFICATION

Input Voltage	100 Vac-240 Vac
Wattage	400W
Form Factor	1U
MTBF(hrs)	100,000 @25°C
Temperature/Humidity	Operating: -10°C ~ 50°C, 85%RH Storage: -40°C ~ 80°C, 95%RH
EMC & Safety	CE, FCC, UL, CSA, TUV, CCC
Dimension (WxHxD)	100 x 40.5 x 190 (mm)

DC OUTPUT

	+5V	+3.3V	-5V	+12V	-12V	+5Vsb
Max. Load	16A	14A	0.1A	33A	0.3A	3A
	85W Max					
Min. Load	0A	0A	0A	0.05A	0A	0A
Ripple	50mv	50mv	100mv	120mv	120mv	50mv