

APD-2022

300W 24V DC input PS/2 ATX Power Supply

FEATURES

- DC input: 19 VDC-32 VDC
- Low ripple & noise output
- Support OVP and SCP
- Safety certifications: CE, FCC, UL, TUV
- Dimension: 150 x 86 x 140 (mm)



SPECIFICATION

Input Voltage	19 VDC-32 VDC
Wattage	300W
Form Factor	PS/2
MTBF(hrs)	100,000 @25°C
Temperature/Humidity	Operating: 0°C ~ 50°C, 5% ~ 95%RH Storage: -40°C ~ 75°C, 5% ~ 95%RH
EMC & Safety	CE, FCC, UL, TUV
Dimension (WxHxD)	150 x 86 x 140 (mm)

DC OUTPUT

	+5V	+3.3V	+12 V1	-5V	-12V	+5Vsb
Max. Load	30A	15A	15A	2A	2A	1.2A
	150W Max					
Min. Load	2A	0A	0.1A	0A	0A	0A
Ripple	50mv	50mv	100mv	100mv	100mv	100mv

APB-3031

500W 2U ATX Power Supply

FEATURES

- Full-range AC input: 115 Vac-230 Vac
- Low ripple & noise output
- Support OVP, SCP, OCP and OTP
- Safety certifications: CE, FCC, CB, BSMI, UL, TUV
- Dimension: 100 x 70 x 245 (mm)



SPECIFICATION

Input Voltage	115 Vac-230 Vac
Wattage	500W
Form Factor	2U
MTBF(hrs)	100,000 @25°C
Temperature/Humidity	Operating: 0°C ~ 50°C, 20% ~ 80%RH Storage: -40°C ~ 85°C, 10% ~ 90%RH
EMC & Safety	CE, FCC, CB, BSMI, UL, TUV
Dimension (WxHxD)	100 x 70 x 245 (mm)

DC OUTPUT

	+5V	+3.3V	+12V1	+12V2	-12V	+5Vsb
Max. Load	20A	20A	20A	20A	0.3A	2.5A
	100W		480W			
Min. Load	0A	0.5A	0A	0A	0A	0A
Ripple	50mv	50mv	120mv	120mv	120mv	50mv