

APD-3053

500W PS/2 ATX Power Supply



SPECIFICATION

Input Voltage	90Vac~264Vac
Wattage	500W
Form Factor	PS/2
MTBF(hrs)	100,000 @35°C
Temperature/Humidity	Operating: 0°C ~ 50°C, 20% ~ 85%RH Storage: -20°C ~ 60°C, 5% ~ 95%RH
EMC & Safety	CE, FCC, CCC, CB, BSMI, UL, BIS, TUV
Dimension (WxHxD)	150 x 86 x 140 (mm)

DC OUTPUT

	+5V	+3.3V	+12 V1	+12 V2	-12V	+5Vsb
Max. Load	22A	10A	20A	25A	0.3A	2.5A
	130W Max		390W Max		3.6W Max	12.75W Max
Min. Load	0.2A	0.1A	0.075A	0.075A	0A	0A
Ripple	50mv	50mv	120mv	120mv	120mv	50mv

APJ-3041

300W Flex ATX Power Supply



SPECIFICATION

Input Voltage	90Vac~264Vac
Wattage	300W
Form Factor	Flex ATX
MTBF(hrs)	100,000 @25°C
Temperature/Humidity	Operating: 0°C ~ 50°C, 85%RH Storage: -40°C ~ 85°C, 95%RH
EMC & Safety	CE, FCC, TUV, CB, CCC, BSMI, RCM, UL
Dimension (WxHxD)	81.5 x 40.5 x 150 (mm)

DC OUTPUT

	+5V	+3.3V	+12 V1	+12 V2	-12V	+5Vsb
Max. Load	17A	14A	18A	18A	0.8A	2A
	110W Max		252W Max			
Min. Load	0.2A	0.1A	0.1A	0.5A	0A	0A
Ripple	50mv	50mv	120mv	120mv	120mv	50mv