

APD-3092

500W PS/2 ATX Power Supply

FEATURES

- Full-range AC input: 100 Vac-240 Vac
- Low ripple & noise output
- Support OVP, SCP, OCP and OTP
- Safety certifications: CE, FCC, CCC, CB, BSMI, UL, TUV, KC
- 80 PLUS® Gold Certified

SPECIFICATION

Input Voltage	100 Vac-240 Vac
Wattage	500W
Form Factor	PS/2
MTBF(hrs)	700,000 @25°C
Temperature/Humidity	Operating: 0°C ~ 50°C, 8% ~ 90%RH Storage: -20°C ~ 85°C, 5% ~ 90%RH
EMC & Safety	CE, FCC, CCC, CB, BSMI, UL, TUV, KC
Dimension (WxHxD)	150 x 86 x 140 (mm)



DC OUTPUT

	+5V	+3.3V	+12	-12V	+5Vsb
Max. Load	20A	20A	41.7	0.3A	3A
	120W		500W	3.6W	15W
Min. Load	0A	0A	1A	0A	0A
Ripple	50mv	50mv	120mv	120mv	50mv

APJ-3041

300W Flex ATX Power Supply

FEATURES

- Full-range AC input: 100 Vac-240 Vac
- Low ripple & noise output
- Support OVP, SCP and OCP
- Safety certifications: CE, FCC, TUV, CB, CCC, BSMI, RCM
- 80 PLUS® Bronze Certified

SPECIFICATION

Input Voltage	100 Vac-240 Vac
Wattage	300W
Form Factor	Flex ATX
MTBF(hrs)	100,000 @25°C
Temperature/Humidity	Operating: 0°C ~ 50°C, 85%RH Storage: -40°C ~ 85°C, 95%RH
EMC & Safety	CE, FCC, TUV, CB, CCC, BSMI, RCM, UL
Dimension (WxHxD)	81.5 x 40.5 x 150 (mm)



DC OUTPUT

	+5V	+3.3V	+12 V1	+12 V2	-12V	+5Vsb
Max. Load	17A	14A	18A	18A	0.8A	2A
	110W Max		252W Max			
Min. Load	0.2A	0.1A	0.1A	0.5A	0A	0A
Ripple	50mv	50mv	120mv	120mv	120mv	50mv